
Curve PRO 3D 29x24mm

PRODUCT DESCRIPTION

Flexible linear wall grazer with lensed optics. Can flex on both vertical and horizontal planes to deliver wall grazing effect on curved walls and uneven surfaces. Optical grade environmental protection silicone material, salt resistant, acid and alkali corrosion resistance, flame retardant, UV resistant. Optional mounting accessories including adjustable mounting brackets and straight linear profiles available. Optics per 41.5mm spacing + 31.5mm per end cap . 30,000hr life. 400mm bending radius. Max. run length 5m.



MANUFACTURER Ratio

COUNTRY OF ORIGIN Australia

PRODUCT Curve PRO 3D 29x24mm

PRODUCT TYPE Wall

MOUNTING TYPE Surface Mounted

POWER 18W, 24W

LUMINOUS FLUX 850lm-1950lm

CCT 2700K, 3000K, 4000K, 2700-6500K, RGBW

CRI 80

DISTRIBUTION 15°, 18x20°, 20x35°, 20x55°, 30°, 50°

CONTROL Fixed Output, Phase DIM, DALI, Casambi Bluetooth

IP RATING 65

IK RATING 8

WARRANTY 5 Years

MANUFACTURER'S WEBSITE

<https://ratio.lighting/range/curve/curve-pro-3d-29x24mm/>
