


VL9050R – Recessed Diffused

PRODUCT DESCRIPTION

Versatile VL9050 is a fully integrated, continuous linear luminaire system using the latest LED technology. VL9050 can be configured to have any number of different module configurations in the same “run” of luminaires – some of these configurations include;

- LED illumination with diffused cover – up to 2,838 lumens per metre
- LED illumination with continuous linear lens offering 5 beam optics – up to 4,851 lumens per metre
- LED illumination with louver offering a low glare (UGR <19), office compliant and available in 2 optical packages – 60° and 90° – up to 3,025 lumens per metre
- Minispot module
- Track lighting insert
- Up-lighting addition – up to 1,269 lumens per metre
- Blanking cover (for no downward illumination where required)

Versatile VL9050 has fully integrated control gear featuring a ‘Plug+Go’ connection system to enable rapid, no fuss installation – direct to mains power with no remote drivers. All of the Versatile VL9050 family is available in surface mounted, wire suspended or rod suspended versions.



MANUFACTURER Intralux

PRODUCT VL9050R – Recessed Diffused

PRODUCT TYPE Ceiling

POWER 25W/m, 41W/m

LUMINOUS FLUX 1890lm/m, 2838lm/m

CCT 2700K, 3000K, 4000K

CRI 90

DISTRIBUTION 120°

DIFFUSER Opal Diffused

CONTROL Fixed Output, DALI & Push Dim, 1-10V, Casambi

IP RATING 40

SCDM 3

OPERATING TEMPERATURE Max. 40°C

LED LIFETIME L90 B10 > 42,000 hours / L80 B10 > 72,000 hours

WARRANTY 5 Years

MANUFACTURER'S WEBSITE

<https://www.intralux.com/vl9050r-diffused/>